

RUSHFPV MAX SOLO 5.8GHz VTX

ENGINEERING REVIEW REQUIRED

RUSHFPV-branded analog transmitter with SmartAudio control. MAX output depends on heat dissipation; the required regional version and cooling arrangement need confirmation.

VERIFIED SPECIFICATIONS

Output power steps	PIT / 25 mW / 500 mW / 1 W / MAX
Power input	7-36 V
Channels	48CH / 37CH (US)
Antenna interface	MMCX 50Ω
Dimensions	H40mm* W24mm* D10.5mm
Catalog weight	15g (Without cable)
Control protocol	Smart Audio

APPLICATION FIT

- Lawful civilian FPV video-link integration
- Industrial inspection and field operations
- Agricultural and commercial UAV integration

BUYER FIT

- Distributors
- System integrators
- Brand / OEM buyers

PURCHASING INFORMATION

MOQ Confirm in quotation	Sample Subject to review	Lead time Confirm in quotation
OEM / ODM Subject to review	Packaging Confirm in quotation	Project review Subject to review

PROJECT AND APPLICATION BOUNDARY

For lawful civilian and industrial projects. Current product revision, availability, system compatibility, final configuration, destination eligibility and local regulatory suitability require written review before supply.

REQUEST A PROJECT-SPECIFIC QUOTATION

Email 2290901833@qq.com

WhatsApp +86 199 2587 7268

RFQ <https://rotorbridge.com/rfq?product=rushfpv-max-solo&source=verified-brief>



SCAN TO OPEN RFQ